



1201 Maple Creek Lane  
New London, WI 54961

Visit Our Web Page  
[www.ejmetals.com](http://www.ejmetals.com)

(920) 779-9913  
FAX (920) 779-9914

---

## **OPTIONS AVAILABLE FROM PUBLISHED SPECIFICATIONS**

### **HIGH-PRESSURE HOSE REEL**

One (1), additional High Pressure hose reel shall be provided. The reel shall be capable of storing 150 feet of .38" high pressure hose. The reel shall be rated for 3,000 psi working pressure.

The reel shall be equipped with electric rewind with a switch located on the reel frame. A roller assembly shall be provided for the reel.

The high pressure hose reel shall be mounted on the upper portion of the water tank.

### **HIGH PRESSURE HOSE**

The reel shall be equipped with 150 feet of .38" high pressure hose.

### **HIGH PRESSURE NOZZLE**

The high pressure hose shall terminate with a high pressure nozzle assembly, stored near the hose reel. The nozzle shall have three (3) patterns:

- 1) A "DRY FOAM" setting with a minimum pattern width of 3 feet and 30 ft length for heavier foam applications.
- 2) A "WET FOAM" setting with a minimum pattern width of 65° and 18 ft length for wet foam applications.
- 3) A "WET FOAM" straight stream "HIGHLY ATOMIZED" setting capable of discharging a minimum distance of 40 feet.

The discharge type shall be selected by rotating the nozzle to the desired position. The nozzle shall be connected to the hose with a swivel type coupling to allow easy removal for storage or maintenance.

## **NOZZLE STORAGE MOUNT**

An EJM Tri-Plex nozzle mount shall be provided. The nozzle mount shall be fabricated from .125" aluminum and 3.0" ID schedule 40 PVC tube. The nozzle mount shall be attached to the drivers or passengers side of the water tank.

## **CAPTIVE ROLLER EXTENSION**

A hat section, captive roller extension box shall be fabricated. This shall prevent any contact of the high pressure hose to the host truck cab or body. The captive roller extension shall be fabricated on site and the measurements shall be determined at the time of build for proper clearance. The captive roller extension shall be powder coated wrinkle black.

## **WORK LIGHT, LED**

One (1), Whelen model PAR36, round super LED work light shall be provided. The work light(s) shall have a pedestal/swivel surface mount and a black housing. The light shall have white LED's, with an intensity level of 6.

The light shall be controlled by a switch on the light head.

## **AUXILIARY PUMP HONDA 1.0" MINI**

One (1), Auxiliary pump shall be provided. The pump shall be a Honda 25cc light weight general-purpose pump. The pump shall be driven by a Honda GX25 4-stroke engine. The pump shall have the following performance:

2220 GPH @ 51 PSI  
118 foot max. total head  
26 foot suction head  
1.0" suction and discharge ports

The pump shall include:

A 15 suction hose and strainer assembly.

A short 1.0" suction hose attached to the tee, on the 1.0" water tank out-let, to allow drafting from the water tank while the auxiliary Honda mini-pump is mounted.

Dimensions: 12.8" long x 8.7" wide x 11.8" high. @ 22 lbs.

This pump will be mounted on a fabricated aluminum bracket powder coat finish, job color. The pump also comes standard with 50' of 1" diameter forestry hose.

CALL FOR PRICING 920-779-9913 EMAIL KEVINJ@EJMETALS.COM